

# Halogen Lamps

MR11, MR16, Halogen, and Par Halogen



LIGHTING PRODUCTS

## Applications



- Residential
- Retail
- Restaurants
- Galleries
- Security
- Floods

**HOWARD**<sup>TM</sup>  
LIGHTING PRODUCTS

*Lighting for life.*

Visit us online at [HowardLightingProducts.com](http://HowardLightingProducts.com) or call us at 800.956.3456.



# Howard's best-in-class halogen lamps.

Howard Lighting Products offers an extensive line of halogen lamps perfect for any application. These highly-efficient lamps promote precision light control and have a high quality reflector coating that minimizes color shift and prevents fading, peeling, and chipping. Made from heavy-duty glass, our lamps are more durable and have a longer life which reduces maintenance costs significantly. Let us help you look your best with halogen lights that provide smoother, more even illumination where you need it most.



MR11



MR16



Lighting **for life**™

Visit us online at [HowardLightingProducts.com](http://HowardLightingProducts.com) or call us at 800.956.3456.

Experience the  
**Howard advantage.**

**HOWARD**<sup>TM</sup>  
LIGHTING PRODUCTS

**HI** A Division of Howard Industries, Inc.



PAR Halogen



Halogen

**We make ordering as easy as 1-2-3.**

**1. Order Direct**  
Contact the authorized agent that you have purchased from in the past.

**2. Order by phone**  
You can also contact us at 800.956.3456 to discuss your needs or place an order.

**3. Order by fax**  
Or if you prefer, you can reach us by fax at 601.422.1652.

# Product Offerings

Watts	UPC #	Howard Catalog #	Base	Volts	Beam Spread	MOL (in)	Dia. (in)	Filament	CBCP	Beam Angle Degree	Avg. Life (hours)	Pkg. Qty.
<b>MR11 Standard Dichroic Open Reflector</b>												
20	799385-01577	20MR11/NSP(FTB)	GU4	12	NSP	1.38	1.38	C-8	4800	10	2000	20
20	799385-01578	20MR11/NFL(FTC)	GU4	12	NFL	1.38	1.38	C-8	1550	20	2000	20
20	799385-01579	20MR11/FL(FTD)	GU4	12	FL	1.38	1.38	C-8	600	30	2000	20
35	799385-01580	35MR11/NSP(FTE)	GU4	12	NSP	1.38	1.38	C-8	7500	10	2000	20
35	799385-01581	35MR11/NFL(FTF)	GU4	12	NFL	1.38	1.38	C-8	3000	20	2000	20
35	799385-01582	35MR11/FL(FTH)	GU4	12	FL	1.38	1.38	C-8	1200	30	2000	20
<b>MR11 Covered Dichroic Reflector (Lensed)</b>												
20	799385-01583	20MR11/NSP/C(FTB-C)	GU4	12	NSP	1.38	1.38	C-8	4800	10	2000	20
20	799385-01584	20MR11/NFL/C(FTC-C)	GU4	12	NFL	1.38	1.38	C-8	1550	20	2000	20
20	799385-01585	20MR11/FL/C(FTD-C)	GU4	12	FL	1.38	1.38	C-8	600	30	2000	20
35	799385-01586	35MR11/NSP/C(FTE-C)	GU4	12	NSP	1.38	1.38	C-8	7500	10	2000	20
35	799385-01587	35MR11/NFL/C(FTF-C)	GU4	12	NFL	1.38	1.38	C-8	3000	20	2000	20
35	799385-01588	35MR11/FL/C(FTH-C)	GU4	12	FL	1.38	1.38	C-8	1200	30	2000	20
<b>MR16 Standard Dichroic Open Reflector</b>												
20	799385-01589	20MR16/NSP(ESX)	GU5.3	12	NSP	1.77	2	C-8	3300	12	2000	20
20	799385-01590	20MR16/FL(BAB)	GU5.3	12	FL	1.77	2	C-8	460	36	2000	20
35	799385-01591	35MR16/NSP(FMT)	GU5.3	12	NSP	1.77	2	C-8	6300	12	2000	20
35	799385-01592	35MR16/NFL(FMV)	GU5.3	12	NFL	1.77	2	C-8	3600	24	2000	20
35	799385-01593	35MR16/FL(FMW)	GU5.3	12	FL	1.77	2	C-8	730	36	2000	20
50	799385-01594	50MR16/NSP(EXT)	GU5.3	12	NSP	1.77	2	C-8	9150	12	2000	20
50	799385-01595	50MR16/NFL(EXZ)	GU5.3	12	NFL	1.77	2	C-8	3000	24	2000	20
50	799385-01596	50MR16/FL(EXN)	GU5.3	12	FL	1.77	2	C-8	1500	36	2000	20
50	799385-01597	50MR16/WFL(FNV)	GU5.3	12	WFL	1.77	2	C-8	750	60	2000	20
75	799385-01598	75MR16/NSP(EYF)	GU5.3	12	NSP	1.77	2	C-8	11500	12	2000	20
75	799385-01599	75MR16/NFL(EYJ)	GU5.3	12	NFL	1.77	2	C-8	4600	24	2000	20
75	799385-01600	75MR16/FL(EYC)	GU5.3	12	FL	1.77	2	C-8	2000	36	2000	20
<b>MR16 Covered Dichroic Reflector (Lensed)</b>												
20	799385-01231	20MR16/NSP/C(ESX-C)	GU5.3	12	NSP	1.77	2	C-8	3300	12	2000	20
20	799385-01252	20MR16/FL/C(BAB-C)	GU5.3	12	FL	1.77	2	C-8	460	36	2000	20
35	799385-01253	35MR16/NSP/C(FMT-C)	GU5.3	12	NSP	1.77	2	C-8	6300	12	2000	20
35	799385-01601	35MR16/NFL/C(FMV-C)	GU5.3	12	NFL	1.77	2	C-8	3600	24	2000	20
35	799385-01602	35MR16/FL/C(FMW-C)	GU5.3	12	FL	1.77	2	C-8	730	36	2000	20
50	799385-01603	50MR16/NSP/C(EXT-C)	GU5.3	12	NSP	1.77	2	C-8	9150	12	2000	20
50	799385-01604	50MR16/NFL/C(EXZ-C)	GU5.3	12	NFL	1.77	2	C-8	3000	24	2000	20
50	799385-01605	50MR16/FL/C(EXN-C)	GU5.3	12	FL	1.77	2	C-8	1500	36	2000	20
50	799385-01606	50MR16/WFL/C(FNV-C)	GU5.3	12	WFL	1.77	2	C-8	750	60	2000	20
75	799385-01607	75MR16/NSP/C(EYF-C)	GU5.3	12	NSP	1.77	2	C-8	11500	12	2000	20
75	799385-01608	75MR16/NFL/C(EYJ-C)	GU5.3	12	NFL	1.77	2	C-8	4600	24	2000	20
75	799385-01609	75MR16/FL/C(EYC-C)	GU5.3	12	FL	1.77	2	C-8	2000	36	2000	20

• Specifications and case quantities are subject to change without notice.



# Product Offerings

Watts	UPC #	Howard Catalog #	Base	Volts	Beam Spread	MOL (in)	Dia. (in)	Filament	Approx. Lumens Initial (lm)	Beam Angle Degree	Avg. Life (hours)	Pkg. Qty.
<b>Par 16 Halogen Medium Screw Base</b>												
60	799385-01644	60PAR16/H/NSP-130 @ 120 volts, approximate 53 watts, 515 lumens, 5000 hours	Med. (E26)	130	NSP	2.88	2	CC-8	660	12	2500	40
60	799385-01645	60PAR16/H/FL-130 @ 120 volts, approximate 53 watts, 515 lumens, 5000 hours	Med. (E26)	130	FL	2.88	2	CC-8	660	36	2500	40
75	799385-01646	75PAR16/H/NSP-130 @ 120 volts, approximate 66 watts, 663 lumens, 5000 hours	Med. (E26)	130	NSP	2.88	2	CC-8	850	12	2500	40
75	799385-01647	75PAR16/H/FL-130 @ 120 volts, approximate 66 watts, 663 lumens, 5000 hours	Med. (E26)	130	FL	2.88	2	CC-8	850	36	2500	40
<b>Par 20 Halogen Medium Screw Base</b>												
35	799385-01296	35PAR20/H/SP-130 @ 120 volts, approximate 31 watts, 281 lumens, 5000 hours	Med. (E26)	130	SP	3.31	2.5	CC-8	360	12	2500	30
35	799385-01298	35PAR20/H/NFL-130 @ 120 volts, approximate 31 watts, 281 lumens, 5000 hours	Med. (E26)	130	NFL	3.31	2.5	CC-8	360	24	2500	30
35	799385-01300	35PAR20/H/FL-130 @ 120 volts, approximate 31 watts, 281 lumens, 5000 hours	Med. (E26)	130	FL	3.31	2.5	CC-8	360	36	2500	30
50	799385-01302	50PAR20/H/SP-130 @ 120 volts, approximate 44 watts, 406 lumens, 5000 hours	Med. (E26)	130	SP	3.31	2.5	CC-8	520	12	2500	30
50	799385-01304	50PAR20/H/NFL-130 @ 120 volts, approximate 44 watts, 406 lumens, 5000 hours	Med. (E26)	130	NFL	3.31	2.5	CC-8	520	24	2500	30
50	799385-01306	50PAR20/H/FL-130 @ 120 volts, approximate 44 watts, 406 lumens, 5000 hours	Med. (E26)	130	FL	3.31	2.5	CC-8	520	36	2500	30
<b>Par 30 Halogen Medium Screw Base</b>												
50	799385-01308	50PAR30/H/SP-130 @ 120 volts, approximate 44 watts, 468 lumens, 5000 hours	Med. (E26)	130	SP	3.6	3.7	CC-8	600	12	2500	30
50	799385-01310	50PAR30/H/NFL-130 @ 120 volts, approximate 44 watts, 468 lumens, 5000 hours	Med. (E26)	130	NFL	3.6	3.7	CC-8	600	24	2500	30
50	799385-01312	50PAR30/H/FL-130 @ 120 volts, approximate 44 watts, 468 lumens, 5000 hours	Med. (E26)	130	FL	3.6	3.7	CC-8	600	36	2500	30
60	799385-01648	60PAR30/H/SP-130 @ 120 volts, approximate 53 watts, 671 lumens, 5000 hours	Med. (E26)	130	SP	3.6	3.7	CC-8	860	12	2500	30
60	799385-01649	60PAR30/H/NFL-130 @ 120 volts, approximate 53 watts, 671 lumens, 5000 hours	Med. (E26)	130	NFL	3.6	3.7	CC-8	860	24	2500	30
60	799385-01650	60PAR30/H/FL-130 @ 120 volts, approximate 53 watts, 671 lumens, 5000 hours	Med. (E26)	130	FL	3.6	3.7	CC-8	860	36	2500	30
75	799385-01314	75PAR30/H/SP-130 @ 120 volts, approximate 66 watts, 764 lumens, 5000 hours	Med. (E26)	130	SP	3.6	3.7	CC-8	980	12	2500	30
75	799385-01316	75PAR30/H/NFL-130 @ 120 volts, approximate 66 watts, 764 lumens, 5000 hours	Med. (E26)	130	NFL	3.6	3.7	CC-8	980	24	2500	30
75	799385-01318	75PAR30/H/FL-130 @ 120 volts, approximate 66 watts, 764 lumens, 5000 hours	Med. (E26)	130	FL	3.6	3.7	CC-8	980	36	2500	30

• Specifications and case quantities are subject to change without notice.



Lighting **for** life.

**HOWARD**<sup>TM</sup>  
LIGHTING PRODUCTS

www.HowardLightingProducts.com • 800.956.3456 • 601.422.1652 (fax)

# Product Offerings

Watts	UPC #	Howard Catalog #	Base	Volts	Beam Spread	MOL (in)	Dia. (in)	Filament	Approx. Lumens Initial (lm)	Beam Angle Degree	Avg. Life (hours)	Pkg. Qty.
<b>Par 30 Long Neck Halogen Medium Screw Base</b>												
50	799385-01320	50PAR30/LN/H/SP-130 @ 120 volts, approximate 44 watts, 429 lumens, 5000 hours	Med. (E26)	130	SP	4.5	3.74	CC-8	550	12	2500	15
50	799385-01322	50PAR30/LN/H/NFL-130 @ 120 volts, approximate 44 watts, 429 lumens, 5000 hours	Med. (E26)	130	NFL	4.5	3.74	CC-8	550	24	2500	15
50	799385-01324	50PAR30/LN/H/FL-130 @ 120 volts, approximate 44 watts, 429 lumens, 5000 hours	Med. (E26)	130	FL	4.5	3.74	CC-8	550	36	2500	15
75	799385-01326	75PAR30/LN/H/SP-130 @ 120 volts, approximate 66 watts, 764 lumens, 5000 hours	Med. (E26)	130	SP	4.5	3.74	CC-8	980	12	2500	15
75	799385-01328	75PAR30/LN/H/NFL-130 @ 120 volts, approximate 66 watts, 764 lumens, 5000 hours	Med. (E26)	130	NFL	4.5	3.74	CC-8	980	24	2500	15
75	799385-01330	75PAR30/LN/H/FL-130 @ 120 volts, approximate 66 watts, 764 lumens, 5000 hours	Med. (E26)	130	FL	4.5	3.74	CC-8	980	36	2500	15
<b>Par 38 Halogen Medium Screw Base</b>												
45	799385-01332	45PAR38/H/SP-130 @ 120 volts, approximate 40 watts, 406 lumens, 5000 hours	Med. Skt. (E26)	130	SP	5.31	4.76	CC-8	520	12	2500	15
45	799385-01334	45PAR38/H/FL-130 @ 120 volts, approximate 40 watts, 406 lumens, 5000 hours	Med. Skt. (E26)	130	FL	5.31	4.76	CC-8	520	36	2500	15
45	799385-01336	45PAR38/H/WFL-130 @ 120 volts, approximate 40 watts, 406 lumens, 5000 hours	Med. Skt. (E26)	130	WFL	5.31	4.76	CC-8	520	50	2500	15
60	799385-01338	60PAR38/H/SP-130 @ 120 volts, approximate 53 watts, 507 lumens, 5000 hours	Med. Skt. (E26)	130	SP	5.31	4.76	CC-8	650	12	2500	15
60	799385-01340	60PAR38/H/FL-130 @ 120 volts, approximate 53 watts, 507 lumens, 5000 hours	Med. Skt. (E26)	130	FL	5.31	4.76	CC-8	650	36	2500	15
60	799385-01342	60PAR38/H/WFL-130 @ 120 volts, approximate 53 watts, 507 lumens, 5000 hours	Med. Skt. (E26)	130	WFL	5.31	4.76	CC-8	650	50	2500	15
75	799385-01344	75PAR38/H/SP-130 @ 120 volts, approximate 66 watts, 764 lumens, 5000 hours	Med. Skt. (E26)	130	SP	5.31	4.76	CC-8	980	12	2500	15
75	799385-01346	75PAR38/H/FL-130 @ 120 volts, approximate 66 watts, 764 lumens, 5000 hours	Med. Skt. (E26)	130	FL	5.31	4.76	CC-8	980	36	2500	15
75	799385-01348	75PAR38/H/WFL-130 @ 120 volts, approximate 66 watts, 764 lumens, 5000 hours	Med. Skt. (E26)	130	WFL	5.31	4.76	CC-8	980	50	2500	15
90	799385-01350	90PAR38/H/NSP-130 @ 120 volts, approximate 79 watts, 858 lumens, 5000 hours	Med. Skt. (E26)	130	NSP	5.31	4.76	CC-8	1100	8	2500	15
90	799385-01352	90PAR38/H/SP-130 @ 120 volts, approximate 79 watts, 858 lumens, 5000 hours	Med. Skt. (E26)	130	SP	5.31	4.76	CC-8	1100	12	2500	15
90	799385-01354	90PAR38/H/FL-130 @ 120 volts, approximate 79 watts, 858 lumens, 5000 hours	Med. Skt. (E26)	130	FL	5.31	4.76	CC-8	1100	36	2500	15
90	799385-01356	90PAR38/H/WFL-130 @ 120 volts, approximate 79 watts, 858 lumens, 5000 hours	Med. Skt. (E26)	130	WFL	5.31	4.76	CC-8	1100	50	2500	15
100	799385-01680	100PAR38/H/FL-130 @ 120 volts, approximate 88 watts, 936 lumens, 5000 hours	Med. Skt. (E26)	130	FL	5.32	4.76	CC-8	1200	36	2500	15

• Specifications and case quantities are subject to change without notice.



# Product Offerings

Watts	UPC #	Howard Catalog #	Bulb	Base	Volts	Lumens	LCL (in)	MOL (in)	Filament	Description	Avg. Life (hours)	Pkg. Qty.
<b>Halogen JD Series (Single Ended T4)</b>												
75	799385-01802	75Q/CL	T4	E11 Min-Can	120	900	1.38	2.63	CC-8	Clear	2000	100
100	799385-01803	100Q/CL/DC	T4	DC Bayonet (BA15d)	120	1200	1.38	2.63	CC-8	Clear	2000	100
100	799385-01804	100Q/CL	T4	E11 Min-Can	120	1200	1.38	2.63	CC-8	Clear	2000	100
150	799385-01805	150Q/CL/DC	T4	DC Bayonet (BA15d)	120	2100	1.38	2.63	CC-8	Clear	2000	100
150	799385-01806	150Q/CL	T4	E11 Min-Can	120	2100	1.38	2.63	CC-8	Clear	2000	100
250	799385-01807	250Q/CL/DC	T4	DC Bayonet (BA15d)	120	4500	1.38	2.63	CC-8	Clear	2000	100
250	799385-01808	250Q/CL	T4	E11 Min-Can	120	4500	1.38	2.63	CC-8	Clear	2000	100
<b>Halogen J Series (Double Ended T3)</b>												
100	799385-01810	100T3Q/CL/S	T3	RSC	130	1400	-	3.13	CC-8	Clear	2000	100
150	799385-01811	150T3Q/CL/S	T3	RSC	130	2400	-	3.13	CC-8	Clear	2000	100
150	799385-01812	150T3Q/CL	T3	RSC	130	2400	-	4.69	C-8	Clear	2000	100
300	799385-01813	300T3Q/CL	T3	RSC	130	5950	-	4.69	C-8	Clear	2000	100
500	799385-01814	500T3Q/CL	T3	RSC	130	10500	-	4.69	C-8	Clear	2000	100
1000	799385-01815	1000T3Q/CL	T3	RSC	240	21000	-	10.13	C-8	Clear	2000	50
1500	799385-01816	1500T3Q/CL	T3	RSC	240	33000	-	10.13	C-8	Clear	2000	50
1500	799385-01817	1500T3Q/CL/277	T3	RSC	277	33000	-	10.13	C-8	Clear	2000	50
<b>Halogen JC Series (Only for Use in Approved Enclosed Halogen Fixtures)</b>												
5	799385-01818	5T3Q/CL	T3	G4	12	60	.88	1.25	C-6	Clear	2000	100
10	799385-01819	10T3Q/CL	T3	G4	12	120	.88	1.25	C-6	Clear	2000	100
20	799385-01820	20T3Q/CL	T3	G4	12	350	.88	1.25	C-6	Clear	2000	100
50	799385-01821	50T4Q/CL	T4	G6.35	12	900	1.13	1.75	C-6	Clear	2000	100
75	799385-01822	75T4Q/CL	T4	G6.35	12	1350	1.13	1.75	C-6	Clear	2000	100
<b>Halogen JCD Series (Only for Use in Approved Enclosed Halogen Fixtures)</b>												
50	799385-01823	50T4Q/CL/G8	T4	G8	120	950	1.13	1.75	CC-2	Clear	2000	100
75	799385-01824	75T4Q/CL/G8	T4	G8	120	1300	1.13	1.75	CC-2	Clear	2000	100
100	799385-01825	100T4Q/CL/G8	T4	G8	120	1900	1.13	1.75	CC-2	Clear	2000	100

• Specifications and case quantities are subject to change without notice.

*introducing...*

<http://www.howard.com/>



Did you know we also offer more than 190,000 technology products? Visit our new Howard Technology website for all of your business or home technology needs.



**Over 190,000 technology products... take your time.**



Lighting **for** life.

**HOWARD**<sup>TM</sup>  
LIGHTING PRODUCTS

www.HowardLightingProducts.com • 800.956.3456 • 601.422.1652 (fax)

# Cross Reference

Watts	Howard	GE	Halco	Philips	SLI	Sylvania	USHIO
<b>MR11 Standard Dichroic Open Reflector</b>							
20	20MR11/NSP(FTB)	N/A	N/A	N/A	20MR11/SP FTB	20MR11/SP10(FTB)	FTB, JDR/M12V-20W/G/NSP
20	20MR11/NFL(FTC)	Q20MR11/SP15	N/A	N/A	20MR11/NFL FTC	N/A	FTC, JDR/M12V-20W/G/SP
20	20MR11/FL(FTD)	Q20MR11/NFL30	N/A	N/A	20MR11/FL FTD	20MR11/FL35(FTD)	FTD, JDR/M12V-20W/G/NFL
35	35MR11/NSP(FTE)	N/A	N/A	N/A	35MR11/SP FTE	35MR11/SP(FTE)	FTE, JDR/M12V-35W/G/NSP
35	35MR11/NFL(FTF)	Q35MR11SP20	N/A	N/A	35MR11/NFL FTF	N/A	FTF, JDR/M12V-35W/G/SP
35	35MR11/FL(FTH)	Q35MR11NFL30	N/A	N/A	35MR11/FL FTH	35MR11/FL35(FTH)	FTH, JDR/M12V-35W/G/NFL
<b>MR11 Covered Dichroic Reflector (Lensed)</b>							
20	20MR11/NSP/C(FTB-C)	N/A	MR11FTB/L	20MRC11/SP10 PRO FTB	Q20MR11/SP/C	N/A	FTB/FG, JDR/M12V-20W/G/NSP/FG
20	20MR11/NFL/C(FTC-C)	N/A	MR11FTC/L	N/A	N/A	N/A	FTC/FG, JDR/M12V-20W/G/SP/FG
20	20MR11/FL/C(FTD-C)	N/A	MR11FTD/L	20MRC11/FL30 PRO FTD	Q20MR11/FL/C	20MR11/FL35/C(FTD)	FTD/FG, JDR/M12V-20W/G/NFL/FG
35	35MR11/NSP/C(FTE-C)	Q35MR11/CG12	MR11FTE/L	N/A	Q35MR11/SP/C	N/A	FTE/FG, JDR/M12V-35W/G/NSP/FG
35	35MR11/NFL/C(FTF-C)	N/A	MR11FTF/L	N/A	N/A	N/A	FTF/FG, JDR/M12V-35W/G/SP/FG
35	35MR11/FL/C(FTH-C)	Q35MR11/CG30	MR11FTH/L	N/A	Q35MR11/FL/C	N/A	FTH/FG, JDR/M12V-35W/G/NFL/FG
<b>MR16 Standard Dichroic Open Reflector</b>							
20	20MR16/NSP(ESX)	Q20MR16/SP	MR16ESX	20MR16/SP10 ESX	Q20MR16/NSP ESX	20MR16/NSP8(ESX)	ESX, JR12V-20W/SP12
20	20MR16/FL(BAB)	Q20MR16/FL	MR16BAB	20MR16/FL36 BAB	Q20MR16/FL BAB	20MR16/FL40(BAB)	BAB, JR12V-20W/FL36
35	35MR16/NSP(FMT)	N/A	N/A	35MR16/SP10	N/A	35MR16/NSP8(FRB)	FMT, JR12V-35W/SP12
35	35MR16/NFL(FMV)	Q35MR16/C/SP20	N/A	35MRC16/NFL24	N/A	35MR16/SP20(FRA)	FMV, JR12V-35W/NFL24
35	35MR16/FL(FMW)	Q35MR16/C/FL40	MR16FMW	35MR16/FL36	N/A	35MR16/FL40(FMW)	FMW, JR12V-35W/FL36
50	50MR16/NSP(EXT)	Q50MR16/SP	MR16EXT	50MR16/SP10 EXT	Q50MR16/NSP EXT	50MR16/NSP12(EXT)	EXT, JR12V-50W/SP12
50	50MR16/NFL(EXZ)	Q50MR16/C/NFL25	MR16EXZ	50MR16/NFL24 EXZ	Q50MR16/NFL EXZ	50MR16/NFL25(EXZ)	EXZ, JR12V-50W/NFL24
50	50MR16/FL(EXN)	Q50MR16/FL	MR16EXN	50MR16/FL36 EXN	Q50MR16/WFL EXN	50MR16/FL40(EXN)	EXN, JR12V-50W/FL36
50	50MR16/WFL(FNV)	Q50MR16/C/WFL55	MR16FNV/U	N/A	N/A	50MR16/VWFL60(FNV)	FNV, JR12V-50W/WFL60
75	75MR16/NSP(EYF)	Q71MR16/C/NSP15	MR16EYF/SC	75MR16/SP10 EYF	N/A	65MR16/NSP10(FPA)	EYF, JR12V-75W/SP12
75	75MR16/NFL(EYJ)	Q71MR16/C/NFL25	MR16EYJ/SC	N/A	N/A	65MR16/NFL25(FPC)	EYJ/EZZ, JR12V-75W/NFL24
75	75MR16/FL(EYC)	Q71MR16/C/FL40	MR16EYC/SC	75MR16/FL36 EYC	Q75MR16/WFL EYC	65MR16/FL40(FPB)	EYC, JR12V-75W/FL36
<b>MR16 Standard Dichroic Open Reflector</b>							
20	20MR16/NSP/C(ESX-C)	Q20MR16C/CG15	MR16ESX/L	N/A	20MR16/SP/10/C	20MR16/B/NSP8/C	ESX/FG, JR12V-20W/SP12/FG
20	20MR16/FL/C(BAB-C)	Q20MR16C/CG40	MR16BAB/L	N/A	20MR16/FL/38/C	20MR16/B/FL35/C	BAB/FG, JR12V-20W/FL36/FG
35	35MR16/NSP/C(FMT-C)	Q35MR16C/CG12	N/A	N/A	35MR16/SP/10/C	35MR16/B/NSP8/C	FMT/FG, JR12V-35W/SP12/FG
35	35MR16/NFL/C(FMV-C)	Q35MR16C/CG20	N/A	N/A	N/A	N/A	FMV/FG, JR12V-35W/NFL24/FG
35	35MR16/FL/C(FMW-C)	Q35MR16C/CG40	MR16FMW/L	N/A	35MR16/FL/38/C	N/A	FMW/FG, JR12V-35W/FL36/FG
50	50MR16/NSP/C(EXT-C)	Q50MR16C/CG15	MR16EXT/L	N/A	50MR16/SP/10/C	50MR16/B/NSP11/C	EXT/FG, JR12V-50W/SP12/FG
50	50MR16/NFL/C(EXZ-C)	Q50MR16C/CG25	MR16EXZ/L	N/A	50MR16/NFL/24/C	N/A	EXZ/FG, JR12V-50W/NFL24/FG
50	50MR16/FL/C(EXN-C)	Q50MR16C/CG40	MR16EXN/L	N/A	50MR16/FL/38/C	50MR16/B/FL35/C	EXN/FG, JR12V-50W/FL36/FG
50	50MR16/WFL/C(FNV-C)	Q50MR16C/CG55	MR16FNV/L/SC	N/A	50MR16/WFL/60/C	N/A	FNV/FG, JR12V-50W/WFL60/FG
75	75MR16/NSP/C(EYF-C)	Q71MR16C/CG15	N/A	N/A	N/A	N/A	EYF/FG, JR12V-75W/SP12/FG
75	75MR16/NFL/C(EYJ-C)	Q71MR16C/CG25	N/A	N/A	N/A	N/A	EYJ/EZZ/FG, JR12V-75W/NFL24/FG
75	75MR16/FL/C(EYC-C)	Q71MR16C/CG40	N/A	N/A	N/A	N/A	EYC/FG, JR12V-75W/FL36/FG



# Cross Reference

Watts	Howard	GE	Halco	Philips	SLI	Sylvania	USHIO
<b>Par 16 Halogen Medium Screw Base</b>							
60	60PAR16/H/NSP-130	N/A	HP16NSP60	60PAR16/HAL/SP10 - 130	N/A	60PAR16/CAP/NSP10 - 130	N/A
60	60PAR16/H/FL-130	N/A	HP16NNFL	60PAR16/HAL/FL27 - 130	N/A	60PAR16/CAP/NFL30 - 130	N/A
75	75PAR16/H/NSP-130	N/A	N/A	N/A	N/A	75PAR16/CAP/NSP10 - 130	N/A
75	75PAR16/H/FL-130	N/A	N/A	N/A	N/A	75PAR16/CAP/NFL30 - 130	N/A
<b>Par 20 Halogen Medium Screw Base</b>							
35	35PAR20/H/SP-130	N/A	N/A	N/A	N/A	35PAR20/CAP/SPL/NSP10	N/A
35	35PAR20/H/NFL-130	N/A	N/A	N/A	N/A	35PAR20/CAP/SPL/NFL30	N/A
35	35PAR20/H/FL-130	N/A	N/A	N/A	N/A	35PAR20/CAP/SPL/WFL40	N/A
50	50PAR20/H/SP-130	50PAR20/H/SP10	HP20SP50	N/A	H50PAR20/SP/130	50PAR20/HAL/SPL/NSP10	50PAR20/SP10/130V
50	50PAR20/H/NFL-130	50PAR20/H/FL25	HP20NFL50/M130	N/A	H50PAR20/FL/130	50PAR20/HAL/SPL/NFL30	50PAR20/NFL30/130V
50	50PAR20/H/FL-130	N/A	N/A	50PAR20/HAL/NFL30	N/A	N/A	50PAR20/FL40/130V
<b>Par 30 Halogen Medium Screw Base</b>							
50	50PAR30/H/SP-130	50PAR30/H/SP10	HP30SP50	50PAR30S/HAL/NSP10	H50PAR30/SP/130	50PAR30/CAP/SPL/NSP9	50PAR30/SP10/130V
50	50PAR30/H/NFL-130	50PAR30/H/FL25	N/A	50PAR30S/HAL/NFL30	H50PAR30/FL/130	50PAR30/CAP/SPL/NFL25	50PAR30/NFL30/130V
50	50PAR30/H/FL-130	50PAR30/H/FL35	HP30FL50/M130	50PAR30S/HAL/FL40	H50PAR30/WFL/130	50PAR30/CAP/SPL/FL40	50PAR30FL40/130V
75	75PAR30/H/SP-130	75PAR30/H/SP10	HP30NSP75	N/A	H75PAR30/SP/130	75PAR30/CAP/SPL/NSP9	75PAR30/SP10/130V
75	75PAR30/H/NFL-130	N/A	N/A	75PAR30S/HAL/NFL30	H75PAR30/FL/130	75PAR30/CAP/SPL/NFL25	75PAR30/NFL30/130V
75	75PAR30/H/FL-130	75PAR30/H/FL35	HP30FL75/M130	75PAR30S/HAL/FL40	H75PAR30/WFL/130	75PAR30/CAP/SPL/FL40	75PAR30/FL40/130V
<b>Par 30 Long Neck Halogen Medium Screw Base</b>							
50	50PAR30/LN/H/SP-130	50PAR30L/H/SP10	HP30SP50L	N/A	N/A	50PAR30LN/CAP/SPL/NSP9	50PAR30LN/SP10/130V
50	50PAR30/LN/H/NFL-130	N/A	N/A	50PAR30L/HAL/NFL30	N/A	50PAR30LN/CAP/SPL/NFL25	50PAR30LN/NFL30/130V
50	50PAR30/LN/H/FL-130	50PAR30L/H/FL40	HP30FL50L	50PAR30L/HAL/FL40	H50PAR30/LN/WFL/130(2)	50PAR30LN/CAP/SPL/WFL50	50PAR30LN/FL40/130V
75	75PAR30/LN/H/SP-130	75PAR30L/H/SP10	HP30SP75L	N/A	N/A	75PAR30LN/CAP/SPL/NSP9	75PAR30LN/SP10/130V
75	75PAR30/LN/H/NFL-130	75PAR30L/H/FL25	N/A	75PAR30L/HAL/NFL30	N/A	75PAR30LN/CAP/SPL/NFL25	75PAR30LN/NFL30/130V
75	75PAR30/LN/H/FL-130	N/A	HP30FL75L	75PAR30L/HAL/FL40	H75PAR30/LN/WFL/130(2)	75PAR30LN/CAP/SPL/WFL50	75PAR30LN/FL40/130V
<b>Par 38 Long Halogen Medium Screw Base</b>							
45	45PAR38/H/SP-130	45PAR/H/SP10	HP38SP45	45PAR38/HAL/SP12	H45PAR38/SP/130	45PAR38/CAP/SPL/SP9	45PAR38/SP10/130V
45	45PAR38/H/FL-130	45PAR/H/FL25	HP38FL45	45PAR38/HAL/FL28	H45PAR38/FL/130	45PAR38/CAP/SPL/FL30	45PAR38/FL30/130V
45	45PAR38/H/WFL-130	N/A	N/A	N/A	N/A	45PAR38/CAP/SPL/WFL50	45PAR38/WFL50/130V
60	60PAR38/H/SP-130	60PAR/H/SP10	N/A	60PAR38/HAL/SP12/WLL	H60PAR38/SP/130	N/A	60PAR38/SP10/130V
60	60PAR38/H/FL-130	60PAR/H/FL25	HP38FL60	60PAR38/HAL/FL28/WLL	H60PAR38/FL/130	60PAR38/CAP/SPL/FL30	60PAR38/FL30/130V
60	60PAR38/H/WFL-130	N/A	N/A	60PAR38/HAL/WFL	N/A	N/A	N/A
75	75PAR38/H/SP-130	N/A	N/A	75PAR38/HAL/SP10/WLL	H75PAR38/SP/130	N/A	75PAR38/SP10/130V
75	75PAR38/H/FL-130	75PAR/H/FL25	HP38FL75	75PAR38/HAL/FL28/WLL	H75PAR38/FL/130	75PAR38/CAP/SPL/FL30	75PAR38/FL30/130V
75	75PAR38/H/WFL-130	N/A	N/A	N/A	N/A	75PAR38/CAP/SPL/WFL50	N/A
90	90PAR38/H/NSP-130	N/A	N/A	N/A	N/A	90PAR38/CAP/SPL/SP9	N/A
90	90PAR38/H/SP-130	90PAR/H/SP10	HP38SP90	90PAR38/HAL/SP12/LL	H90PAR38/SP/130	90PAR38/CAP/SPL/WSP12	90PAR38/SP10/130V
90	90PAR38/H/FL-130	90PAR/H/FL25	HP38FL90	90PAR38/HAL/FL28/LL	H90PAR38/FL/130	90PAR38/CAP/SPL/FL30	90PAR38/FL30/130V
90	90PAR38/H/WFL-130	N/A	N/A	90PAR38/HAL/WFL/LL	N/A	90PAR38/CAP/SPL/WFL50	90PAR38/WFL50/130V
100	100PAR38/H/FL-130	100PAR/H/FL25	N/A	N/A	N/A	N/A	N/A



Lighting for life.

**HOWARD**<sup>TM</sup>  
LIGHTING PRODUCTS

# Cross Reference

Watts	Howard	GE	Halco	Philips	SLI	Sylvania	USHIO
<b>Par 36 Screw Terminal Base</b>							
36	36PAR36/H/VNSP	35PAR36/H/SP5	HP36VNSP35/HX	N/A	N/A	36PAR36/CAP/VNSP5	N/A
36	36PAR36/H/NSP	35PAR36/H/SP8	HP36NSP35/HX	N/A	N/A	36PAR36/CAP/NSP13	N/A
36	36PAR36/H/WFL	35PAR36/H/FL30	HP36WFL35/HX	N/A	N/A	36PAR36/CAP/WFL32	N/A
50	50PAR36/H/VNSP	50PAR36/H/SP5	HP36VNSP50/HX	50PAR36Q/VNSP6	N/A	50PAR36/CAP/NSP6	N/A
50	50PAR36/H/NSP	50PAR36/H/SP8	HP36NSP50/HX	N/A	N/A	N/A	N/A
50	50PAR36/H/WFL	50PAR36/H/FL30	HP36NWFL50/HX	N/A	N/A	N/A	N/A
<b>JD Series (Single Ended T4)</b>							
75	75Q/CL	Q75CL	JD75MC/120	BC75Q/CL	75Q/CL Mini-Can (130V)	75Q/CL/MC/RP	JD120V-75W/ELL
100	100Q/CL/DC	Q100CL/DC	JD100DC/120	100Q/CL/DC ESR	N/A	100Q/CL/DC(ESR)	JD120V-100W/BA15D
100	100Q/CL	Q100CL/MC	JD100MC/120	BC100Q/CL ESN	100Q/CL Mini-Can (130V)	100Q/CL/MC(ESN)	JD120-100W/E11
150	150Q/CL/DC	Q150CL/DC	JD150DC (130V)	150Q/CL/DC ETC	150Q/CL DC Bay (130V)	150Q/CL/DC/1(ESP)	JD120-150W/BA15D
150	150Q/CL	Q150CL/MC	JD150MC/120	150Q/CL	150Q/CL Mini-Can (130V)	150Q/CL/MC/RP(ETG)	JD120-150W/E11
250	250Q/CL/DC	Q250CL/DC	JD250DC/120	250Q/CL/DC ESS	250Q/CL DC Bay (130V)	250Q/CL/DC(ESS)	ESS, JCV120V-250WGB
250	250Q/CL	Q250CL/MC	JD250MC/120	250Q/CL EHT	250Q/CL Mini-Can (130V)	250Q/CL/MC(EHT)	EHT, JCV120V-250WGSN
<b>J Series (Double Ended T3)</b>							
100	100T3Q/CL/S	Q100T3/CL/CD 120V	Q100T3C/S	BC100T3Q/CL (120V)	100T3Q/CL (120V)	100T3Q/CL/RP (120V)	J130V-100W/79MM SHORT
150	150T3Q/CL/S	Q150T3/CL/CD 120V	Q150T3C/S	BC150T3Q/CL (120V)	150T3Q/S/CL (1/CD)	150T3Q/S/CL (120V)	J130V-150W/79MM SHORT
150	150T3Q/CL	Q150T3/117/CL/CD 120V	Q150T3C	BC150T3Q/CL LONG (120V)	N/A	150T3Q/CL/RP (120V)	J130V-150W/119MM LONG
300	300T3Q/CL	Q300T3/CL-6PK 120V	Q300T3C	BC300T3Q/CL (120V)	300T3Q/CL	300T3Q/CL	J130V-300W/119MM LONG
500	500T3Q/CL	Q500T3/CL	Q500T3C	500T3Q/CL 125-130V	500T3Q/CL	500T3Q/CL	DVS, J130V-500WB
1000	1000T3Q/CL	Q1000T3/CL-6PK	Q1000T3C	1000T3Q/CL	N/A	1000T3Q/CL	J240V-1000WB1
1500	1500T3Q/CL	Q1500T3/CL 240V	Q1500T3C	1500T3Q/CL (240V)	1500T3Q/CL-240	1500T3Q/CL	DYD, J240V-1500WB
1500	1500T3Q/CL/277	Q1500T3/CL 277V	Q1500T3C/277	1500T3Q/CL (277V)	1500T3Q/CL-277	1500T3Q/CL277V	J177V-1500WB
<b>JC Series (Only for Use in Approved Enclosed Halogen Fixtures)</b>							
5	5T3Q/CL	Q5T3/CL	JC5	N/A	5T3Q/CL	5T3Q/CL	JC12V-5W/G4
10	10T3Q/CL	Q10T3/CL	JC10	10W/T3/12V	10T3Q/CL	10T3Q/CL	JC12V-10W/G4
20	20T3Q/CL	Q20T3/CL	JC20	20W/T3/12V	20T3Q/CL	20T3Q/CL	JC12V-20W/G4
50	50T4Q/CL	Q50T4/CL/CD	JCD50	50W/T4/12V	50T4Q/CL	50T4Q/CL	JC12V-50WG1.0
75	75T4Q/CL	Q75T4/CL/CD	JCD75	N/A	N/A	75T4Q/CL/RP	JC12V-75W
<b>JCD Series (Only for Use in Approved Enclosed Halogen Fixtures)</b>							
50	50T4Q/CL/G8	Q50G8/CD	JCD50/G8	N/A	N/A	N/A	JCD120V-50W
75	75T4Q/CL/G8	N/A	N/A	N/A	N/A	N/A	JCD120V-75W
100	100T4Q/CL/G8	N/A	JCD100/G8	N/A	N/A	N/A	N/A
90	90PAR38/H/WFL-130	N/A	N/A	90PAR38/HAL/WFL/LL	N/A	90PAR38/CAP/SPL/WFL50	90PAR38/WFL50/130V
100	100PAR38/H/FL-130	100PAR/H/FL25	N/A	N/A	N/A	N/A	N/A



# Are you ready to order?

Visit our website at [www.HowardLightingProducts.com](http://www.HowardLightingProducts.com) to identify the member of our nationwide sales network in your specific area. These trained professionals provide quick turnaround on all quotes and questions in addition to assisting you in the order placement process.

### **How can I reach your customer or technical support team?**

Anytime you have engineering or technical questions regarding one of our products, assistance is just a phone call away. Our customer and technical support is available Monday - Friday 7 AM - 5 PM (CST) at 800.956.3456 or via fax at 601.422.1652. We value our customers and pride ourselves on providing the superior service you would expect from a premier lighting provider.

### **I need my products NOW! Do you offer rapid shipping?**

To ensure you have the products you need when you need them, many of our most popular products are available through our Rapid Shipping Program. Typically, these products are shipped within 24 hours of order receipt. Contact our customer support center for details or refer to our pricing lists.

### **Do you offer distributor packaging?**

Absolutely! We understand the importance of having contractor-friendly distributor packaging which is why ours is heavy duty and has been specifically designed for the electrical and lighting distributor markets.

### **What about your terms and warranty?**

We offer a limited warranty on all of our products.

### **Still need more information?**

To obtain the most up-to-date information about us and our products and services, visit our website at [www.HowardLightingProducts.com](http://www.HowardLightingProducts.com). We are excited about our product offerings and look forward to welcoming you to our Howard Lighting customer family.



Lighting **for life.**

**HOWARD**<sup>™</sup>  
LIGHTING PRODUCTS

In addition to lamps we also offer *lighting fixtures and ballasts!*



With products in use at Johnson Space Center, Kennedy Space Center, Camp Pendleton, CIA headquarters at Langley, Fort Bragg, and numerous other US government facilities, we deliver superior lighting products where you need them the most – *Life.*

# HOWARD™

LIGHTING PRODUCTS

 *A Division of Howard Industries, Inc.*

580 Eastview Drive • Laurel, MS 39443  
P.O. Box 1590 • Laurel, MS 39441

800.956.3456 *general* • 601.422.1652 *fax*  
601.422.0033

[www.HowardLightingProducts.com](http://www.HowardLightingProducts.com)

